

Model: NKR-AC006

AC output:

Single gun or socket for 7/22 kw



Model: NKR-AC006

Features

- 1、OCPP1.6J+
- 2、Type A RCD+DC 6ma
- 3、All components come with CE certificate.
- 4、APP operation
- 5、Ethernet&Wifi&Bluetooth
- 6、Remote monitor&appointment& diagnosis & upgrade

Applications



Specifications

Appearance	Wall Box Dimension	H35*W20*T13.5cm	
	Weight	3-7KG	
	Cable length	≥4.2m (External line)	
	Installation Method	Wall-mounted, Floor stand (Optional)	
	Shell Material	ABS	
Electrical Parameter	Input Voltage	Single phase:230VAC±10%	Three phase:400VAC±10%
	Output Voltage	Single phase:230VAC±10%	Three phase:400VAC±10%
	Output Rating	Type 2:7kw-single phase 32A Type 1:9kw-single phase 40A	Type 2:22kw-three phase 32A
	Input frequency	50Hz/60Hz	
	Precision	Class 1	
	Standby Power	<2w	

Functional Features	Earth Leakage Protection	Type A 30ma ac and 6ma dc
	User Interface	Emergency Stop/LED indicator/RFID
	Safety Features	Over voltage/under voltage protection, overload protection, leakage protection, Over current protection, PEN detection
Communication	Internet Interface	Ethernet, WIFI
	OCPP	OCPP1.6J+
Working environment	Working latitude	<2000m
	Working temperature	-30° C~+55° C
	Working humidity	5 % ~ 95%
	Protection level	IP65
	Cooling	Natural air cooling
Special protection	Anti-UV protection	

Additional Accessories for Options

- 1、Pestle.
- 2、Customized cable length.
- 3、Customized Box color and customized logo
- 4、Rfid
- 5、4G